

最大トルク値と対応ネジ一覧表

ミリ	トルク容量**			対応ネジ				
								
	N・m	N・m	N・m	キャップボルト	皿ボルト	ボタンボルト	止めネジ	シヨルダー
1.27 MM	0.892	0.339	—	M1.4	—	—	M2.5	—
1.5 MM	1.48	0.565	—	M1.6, M2	—	—	M3	—
2 MM	3.729	1.469	—	M2.5	M3	M3	M4	—
2.5 MM	7.119	3.729	—	M3	M4	M2.5	M5	—
3 MM	11.97	5.0	10.6	M4	M5	M5	M6	M5
3.5 MM	16.13	7.91	—	—	—	—	—	—
4 MM	29.83	14.8	27.0	M5	M6	M6	M8	M6
4.5 MM	34.5	16.6	—	—	—	—	—	—
5 MM	54.57	27.91	41.3	M6	M8	M8	M10	M8
5.5 MM	63.24	30.5	—	—	—	—	—	—
6 MM	96.61	44.74	78.0	M8	M10	M10	M12	M10
7 MM	123.2	62.1	122.8	—	—	—	—	—
8 MM	210.2	111.7	184.1	M10	M12	M12	M14, M16	M12
9 MM	262.8	128	—	—	—	—	—	—
10 MM	402.6	179.7	293.8	M12	M14, M16	M14, M16	M18, M20	M16
12 MM	576.6	228.5	—	M14	M18, M20	M18, M20	M22, M24	M20
14 MM	913	363.5	—	M16, M18	M22, M24	M22, M24	—	—
17 MM	1639.1	643.3	—	M20, M22	—	—	—	—
19 MM	2291.9	909.8	—	M24, M27	—	—	—	—
インチ	N・m	N・m	N・m					
0.05 (1.27mm)	0.892	0.339	—	#0	#1, #2	#1, #2	#3, #4	—
1/16 (1.588mm)	1.796	0.791	—	#1	#3, #4	#3, #4	#5, #6	—
5/64 (1.984mm)	3.842	1.469	—	#2, #3	#5, #6	#5, #6	#8	—
3/32 (2.381mm)	5.763	2.712	—	#4, #5	#8	#8	#10	—
7/64 (2.778mm)	9.492	4.407	—	#6	#10	—	—	—
1/8 (3.175mm)	14.57	6.441	11.1	—	—	#10	1/4	1/4
9/64 (3.572mm)	20.9	9.718	17.6	#8	1/4	—	—	—
5/32 (3.969mm)	29.94	14.35	27.0	#10	5/16	1/4	5/16	5/16
3/16 (4.763mm)	48.7	21.35	41.3	1/4	3/8	5/16	3/8	3/8
7/32 (5.556mm)	76.04	35.93	61.8	—	7/16	3/8	7/16	—
1/4 (6.35mm)	107.3	54.44	88.2	5/16	1/2	—	1/2	1/2
5/16 (7.938mm)	228.4	100.3	181.3	3/8	5/8	1/2	5/8	5/8
3/8 (9.525mm)	339.5	168.1	273.4	7/16, 1/2	—	5/8	3/4	3/4
7/16 (11.113mm)	457.3	187.7	—	9/16	3/4	—	—	—
1/2 (12.7mm)	681.7	277	—	5/8	—	—	7/8	1
9/16 (14.288mm)	972.2	390.8	—	—	—	—	1, 1-1/8	—
5/8 (15.875mm)	1335.4	532.3	—	3/4	—	—	1-1/4, 1-3/8	1-1/4
3/4 (19.05mm)	2307.6	909.8	—	7/8, 1	—	—	1-1/2	—
トルクス®								
	N・m	N・m	N・m					
T5 (1.42mm)	0.4	—	—	—	—	—	M3	—
T6 (1.67mm)	0.7	0.45	—	—	#2	—	M4	—
T7 (2mm)	1.4	1.0	—	—	#3	#2	#5, #6	—
T8 (2.3mm)	2.3	1.8	—	—	#4	#3	#8	—
T9 (2.49mm)	2.8	2.1	—	—	#5	#4	—	—
T10 (2.72mm)	3.07	2.8	—	#4, #5, M3	#6	#5	#10, #12	—
T15 (3.26mm)	6.4	4.6	5.4	#6	#8	#6	—	—
T20 (3.84mm)	10.5	6.9	8.9	—	#10	#8	1/4	—
T25 (4.40mm)	15.8	9.6	13.4	#8, M4	#12	#10	—	—
T27 (4.96mm)	22.5	10.8	19.0	#10, #12, M5	1/4	#12	5/16	—
T30 (5.49mm)	31.2	12.4	26.4	1/4, M6	—	1/4	3/8	—
T40 (6.60mm)	54.2	41.0	46.0	—	5/16, 3/8	—	7/16	—
T45 (7.70mm)	86.2	46.2	73.2	5/16, M8	—	3/8	1/2	—
T50 (8.79mm)	132.3	49.7	112.0	3/8, M10	7/16	7/16	—	—
T55 (11.17mm)	218.2	90.3	185.4	7/16, 1/2, M12	1/2	1/2	—	—

※トルクス®とトルクスプラス®はアキュメント社の登録商標です。
 **トルク容量とは、工具が折れる前のトルク値を示しています。